# Storage S2

AIO-10KWH1P2S-CE

With a built-in inverter and latest smart systems, you will be able to harness and maximise your use of renewable energy in a sleek and minimalist form factor.

### **Special Features**

- Easy installation with modular and stacked design.
- High performance charge and discharge.
- Whisper quiet system.
- Independent all-in-one unit with built-in inverter and battery
- Adaptive with self-power, backup and load shifting modes.



All Metal Construction



Cobalt Free LifePO4



Plug and Play Installation



Multi-State Protection



Remote Firmware Upgrade



Smart System



User Friendly App



10 Year Warranty



## Storage S2

Model	AIO-10KWH1P2S-CE
Rated Energy (kWh)	10.2
Usable Energy (kWh)	9.7
Dimensions W*D*H (mm)	730*203*1270
Weight (kg)	122
Communication	RS485
Communication with Portal	Wifi / 4G / Ethernet
Degree of Protection	IP65
Heat Dissipation Method	Natural convection
Operating Temperature Range	-10°C~50°C (45°C~60° Derating)
Relative Humidity	0~95% RH
Warranty	10 years
Mounting Method	Floor standing
Construction	Metal powdercoat
Certification & Standards	CEC, UN 38.3, IEC 62619, IEC 62109, AS/NZS 4777
Display	SOC indicator, status indicator

# Safety and Monitoring

- AC Short-Circuit Protection
- Overload Protection
- Residual Current Detection
- Anti-Island Protection
- AC Surge Protection
- DC Surge Protection
- DC Over-Under-Voltage Protection
- AC Undervoltage Protection
- AC Underfrequency Protection
- PV Anti-Reverse Connect Protect
- DC Disconnect Device
- AC Over Current Protection
- AC Over Voltage Protection
- Over Temp Protection
- Communication Fault Protection

### **Inverter Module**

Rated Output Power (kW)	5
Rated Output Current (A) @230VAC	21.8
Peak Output Power (VA)	6000@10s
Rated Output voltage (V)	230
Phase	Single-phase
Rated Output Frequency (Hz)	50Hz / 60Hz

Backup Power Mode	Yes
Max Input Voltage (V)	600
MPPT Voltage Range (V)	120~550
MPPT Max Input Current (A)	13.5
MPPT Max Short-Circuit Current (A)	15
No. of MPPT Trace Paths	2

## **Battery Pack**

Type of Battery	Lithium Iron Phosphate (LFP)
Rated Energy (kWh) Per Module	5.12
Rated Voltage (V)	51.2
Max Charge/Discharge Current (A)	50/75
Weight (kg) Per Module	48
Max Battery Discharge Efficiency	95%

www.lavo.com.au/lavo-life