

Harvest the Sunshine

490W



JA SOLAR

JAM48D50 LR n-type Double Glass Monofacial Modules



DEEP BLUE 5.0

Intelligent · Quality · Evolution

Premium Modules



Higher Power Output

Bycium+ 5.0 Cell Technology

Superior Full-Screen Design



Enhanced Reliability

Composite Structure
Enhancement Technology




Higher Power Generation

Better Temperature Coefficient ($-0.26\%/^{\circ}\text{C}$)

Excellent Low-Light Performance



Lower LCOE Higher Customer Value




15 15-year product warranty

30 30-year linear power output warranty


*Remark: The performance warranty applies at STC condition.

Comprehensive Certificates

- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing



JAM48D50 LR n-type Double Glass Monofacial Modules



MECHANICAL PARAMETERS

Cell	Mono
Weight	21.5kg
Dimensions	1762mm × 1134mm × 30mm
Cable Cross Section Size	4mm ² (IEC), 12 AWG(UL)
No. of cells	144(6 × 24)
Junction Box	IP68, 3diodes
Connector	Stäubli PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy QC Solar QC4.10-351/ QC4.10-35
Cable Length (Including Connector)	Portrait: 300mm(+)/400mm(-) Landscape: 1200mm(+)/1200mm(-)
Frame	Anodized Aluminium Alloy
Front Glass	1.6mm, Anti-reflection Coating
Back Glass	1.6mm, Heat Strengthened Glass
Packaging Configuration	37pcs/Pallet, 962pcs/40HQ Container
Country of Manufacturer	China/Vietnam

Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC

TYPE	JAM48D50 -475/LR	JAM48D50 -480/LR	JAM48D50 -485/LR	JAM48D50 -490/LR
Rated Maximum Power(P _{max}) [W]	475	480	485	490
Open Circuit Voltage (V _{oc}) [V]	36.33	36.40	36.47	36.53
Maximum Power Voltage(V _{mp}) [V]	29.81	30.04	30.26	30.48
Short Circuit Current(I _{sc}) [A]	16.73	16.78	16.83	16.88
Maximum Power Current(I _{mp}) [A]	15.93	15.98	16.03	16.08
Module Efficiency [%]	23.8	24.0	24.3	24.5
Power Sorting Tolerance	0~+3%			
Temperature Coefficient of I _{sc} /α _{Isc}	+0.041%/°C			
Temperature Coefficient of V _{oc} (β _{Voc})	-0.220%/°C			
Temperature Coefficient of P _{max} (γ _{Pmp})	-0.260%/°C			
STC	Irradiance 1000W/m ² , cell temperature 25°C, AM1.5G			

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.

They only serve for comparison among different module types.


Measurement tolerance at STC and BNPI: P_{max} ±3%, V_{oc} ±3%, I_{sc} ±5% and the tolerance of I_{sc} at BSI: ±5%.

ELECTRICAL PARAMETERS With Low Irradiance Of 200W/m²

TYPE	JAM48D50 -475/LR	JAM48D50 -480/LR	JAM48D50 -485/LR	JAM48D50 -490/LR
Rated Max Power(P _{max}) [W]	92.14	93.14	94.14	94.97
Open Circuit Voltage(V _{oc}) [V]	34.07	34.16	34.24	34.29
Max Power Voltage(V _{mp}) [V]	29.31	29.45	29.56	29.69
Short Circuit Current(I _{sc}) [A]	3.35	3.36	3.37	3.38
Max Power Current(I _{mp}) [A]	3.14	3.16	3.18	3.20
Low Irradiance	(200 ± 2) W/m ² , module at (25 ± 2) °C			

* For Nexttracker installations, maximum static load please take compatibility approve letter between JA Solar and Nexttracker for reference.

CHARACTERISTICS



OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature*	-40°C~+70°C
Maximum Series Fuse Rating	30A
Maximum Static Load, Front**	3600Pa, 1.5
Maximum Static Load, Back**	1600Pa, 1.5
NOCT	45 ± 2 °C
Safety Class	Class II
Fire Performance	UL Type 38/Class C

*PV module 98th percentile operating temperature : 70°C

**3600Pa/1600Pa refers to the design load, 1.5 refers to safety factors



Headquarters

JA Solar Technology Co., Ltd.
No. 8 Building, Nuode Center, No.1 Courtyard, East Auto Museum Road,
Fengtai District, Beijing
Tel: +86 10 6361 1888 Fax: +86 10 6361 1999
E-mail: sales@jasolar.com marketing@jasolar.com www.jasolar.com

Specifications subject to technical changes and tests.
JA Solar reserves the right of final interpretation.

Version No. : Aus-EN-20260612A